



# OLIN

## 120V PENDANTS

### SPECIFICATIONS:

#### DESCRIPTION

Cord-hung or stem-mount pendant with handcrafted glass diffuser.

#### LAMPING

**Standard:** 60W T10 Medium-based 120V, lamp not included. Dimmable with standard incandescent dimmer (not included).

**Plumen:** 9W Plumen CFL Medium-based, 120V, lamp included.

**Edison:** 40W Edison Filament Medium-based, 120V, lamp included.

**LED Edison:** 5W Replaceable S-Style LED Filament lamp, 120V, dimmable, 2700°K CCT, 540 lumens, 15,000 hours, lamp included.

#### DIFFUSER

Shade shall be handcrafted glass of various decors. 7" Dia. x 11" H

#### SUSPENSION

**Cord-hung:** 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Plated stamped steel construction. Bronze or Satin Nickel. See next page for mult light options.

**Stem-mount:** 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.

#### MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.


#### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Consult factory concerning lower wattage labeling for energy requirements.



OLIN SHOWN IN SMOKE (OLINSM)



OLINCL  
CLEAR



OLINAM  
AMBER



OLINFR  
FROST



#### Project Information:

**For ordering information, see next page**

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 1/17



ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
Cord Fixture	<b>OLINAM</b> Amber	(blank) 60W T10 Incan	<b>BR</b> Bronze	<b>L</b> 15' cord
<b>1JC</b> 1 Lt. Dome	<b>OLINCL</b> Clear	<b>PLU</b> 9W Plumen	<b>SN</b> Satin Nickel	<b>LW</b> Low wattage labeling
<b>1JT</b> 1 Lt. Flat	<b>OLINFR</b> Frost	<b>EDI</b> 40W Edison		
	<b>OLINSM</b> Smoke	<b>EDIL</b> 5W LED Filament		

Stem Fixture  
**1TT** 1 Lt. Flat


Multi light  
**J** For Multi light  
Canopy

Multi light available  
See options to right

**Ex. 1JT-OLINCL-SN**  
Olin Pendant w/ Clear Glass,  
Satin Nickel Finish


MULTIPOINT CANOPY OPTIONS:

**T33X** 3 LIGHT ROUND CANOPY




- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights

**T33XL** 3 LIGHT LARGE ROUND CANOPY




- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 16" Dia. shades MAX, with staggered heights

**T36X** 6 LIGHT ROUND CANOPY




- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights

**T39X** 9 LIGHT ROUND CANOPY




- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 10" Dia. shades MAX, with staggered heights

**T33V** 3 LIGHT BAR CANOPY




- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights

**T34V** 4 LIGHT BAR CANOPY



- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 20" Dia. shades MAX, with staggered heights


**T37V** 7 LIGHT BAR CANOPY



- Suitable for sloped ceilings
- Bronze or Satin Nickel
- 14" Dia. shades MAX, with staggered heights


PENDANT OPTIONS:

**1JT / 1JC / J** MONOPOINT PENDANT CANOPY



- Flat (1JT) or Dome (1JC) Canopy styles. Dome style allows adjustment without cutting cord.
- "J" option is pendant less canopy for multipoint canopy (options to the right)
- Suitable for sloped ceilings
- Cord: 10' SVT, 5" sleeve at socketholder (V Series utilizes SJT-type)
- Bronze or Satin Nickel

**1TT** STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- Bronze or Satin Nickel

ACCESSORIES:

**ADDITIONAL STEM SECTIONS:**

Additional connecting stems are available to increase overall length, up to 10' max. Telescoping adjustable section allows up to 3" movement.

- T20A-SN** or **T20A-BR** Adj. Section
- T203-SN** or **T203-BR** 3" Section
- T206-SN** or **T206-BR** 6" Section
- T212-SN** or **T212-BR** 12" Section
- T218-SN** or **T218-BR** 18" Section

**LONGER CORD LENGTHS:**

Longer cord length of 15' available. Add an "L" to the end of the item number, i.e. 1JC-169707-SNL.

**LOW WATTAGE LABELING:**

Incandescent fixture supplied with 16 watt relamp label. Add an "LW" to the end of the item number, i.e. 1JC-169707-SN-LW.

**CORD SLEEVES:**

If concealing the cord is desired, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

- T118-SN** Satin Nickel
- T118-BR** Bronze

**STEMHOOKS:**

Suspension hooks allow cord drops to be placed wherever desired. Suitable for sloped ceilings.

- T103BR** Bronze
- T103SN** Satin Nickel

**HOW TO ORDER A MULTILIGHT FIXTURE**

Order your canopy with the selected 120V multi light pendants (indicated by "B" or "J" prefix) for the complete fixture:

**Example: 1x T33X-SN (3 Light Round Canopy)**

**1x J-OLINAM-SN (Olin Pendant in Amber)**

**1x J-OLINCL-SN (Olin Pendant in Clear)**

**1x J-OLINSM-SN (Olin Pendant in Smoke)**